



INTERMEDIATE PRESSURE LIMITS
 INTERMEDIATE PRESSURES MUST BE
 BETWEEN 128-140 PSIG AT 2,000 PSIG AND BE
 BETWEEN 110 & 130 PSIG AT 300 PSIG. 0 PSIG
 INTERMEDIATE PRESSURE CREEPAGE
 ALLOWED AFTER SEATING OF A NEW SEAT.

ITEM NO.	QTY REQD	PART NO.	DESCRIPTION	SUGG. RETAIL
1	1	01-050-103	O-RING (BLACK)	
2	1	10-103-113	RETAINER, DIN 200 BAR	
3	1	10-103-114	RETAINER, DIN 300 BAR	
4	1	01-050-151	O-RING (RED)	
5	1	01-028-109	FILTER, CONICAL	
6	1	01-073-108	RETAINER	
7	1	10-105-117	KNOB, DIN 200 BAR	
8	1	01-105-116	KNOB, DIN 300 BAR	
9	1	10-043-020	KIT, CONVERSION, 200 BAR DIN	
10	1	10-043-030	KIT, CONVERSION, 300 BAR DIN	
11	1	10-107-111	ADAPTER, FRENCH	
12	1	01-050-144	O-RING (BLUE)	
13	1	01-073-101	RETAINER	
14	1	10-103-112	YOKE RETAINER	
15	1	10-101-130	YOKE SCREW 3/8 THREAD	
16	1	10-101-113	YOKE SCREW 7/16 THREAD	
17	1	10-101-132	YOKE SCREW 9/16 THREAD	
18	1	10-200-008	YOKE SCREW ASSY., 9/16 THREAD	
19	1	10-101-131	YOKE 9/16 THREAD	
20	1	10-101-111	1ST STAGE INLET PROTECTOR	
21	1	10-101-139	PLUG, 7/16-20 HP	
22	1	01-050-138	O-RING (BLUE)	
23	1	10-101-039	PLUG W/O-RING, 7/16-20 HP	
24	1	01-050-342	O-RING (PURPLE)	
25	1	10-101-144	H.P ADAPTER W/O-RING, LG MALE/SM FEMALE THD	
26	1	10-101-044	H.P ADAPTER W/O-RING, LG MALE/SM FEMALE THD	
27	1	10-101-138	H.P ADAPTER W/O-RING, SM MALE/LG FEMALE THD	
28	1	10-101-038	H.P ADAPTER W/O-RING, SM MALE/LG FEMALE THD	
29	1	10-103-110	BODY	
30	3	01-060-103	WASHER (WHITE)	
31	1	10-043-002	SPRING (BLUE)	
32	1	01-060-214	WASHER (BLACK)	
33	1	10-200-107	SEAT	
34	1	01-050-126	O-RING (RED)	
35	1	10-103-102	PISTON	
36	1	01-050-167	O-RING (BLUE)	
37	1	10-103-104	CAP, S.P.E.C.	
38	1	10-103-112	YOKE RETAINER	
39	1	01-028-101	FILTER	
40	2	01-050-132	O-RING (BLUE)	
41	2	10-101-104	PLUG	
42	2	10-101-006	PLUG W/O-RING	
43	1	10-103-010	KIT, S.P.E.C. CAP & ENVIRONMENTAL GREASE	
44	1	41-035-000	ENVIRONMENTAL GREASE, 7 GR.	
45	1	45-103-188	MANUAL	
46	-	10-103-040	REPAIR KIT, ANNUAL	

PRICES SUBJECT TO CHANGE WITHOUT NOTICE
NOTES:

- ① NOT SHOWN
- △ OPTIONAL ITEM
- △ OLDER CONFIGURATION
- △ FOR OLDER CONFIGURATION H.P. HOSES USED W/NEW CONFIGURATION REGULATORS
- △ MAXIMUM 3 WASHERS P/N 01-060-103 WASHERS ARE USED AS SHIMS TO ADJUST THE INTERMEDIATE PRESSURE TO BE WITHIN THE SPECIFIED LIMITS.
- △ NOT COVERED UNDER WARRANTY
- △ USED ONLY FOR 2250 PSI SERVICE CYLINDERS, REFER TO ENGINEERING BULLETIN #170A
- ⊕ ANNUAL REPLACEMENT
- ◇ DYNAMIC O-RING REPLACE ANNUALLY
- <> TORQUE IN INCH POUNDS

MARK III FIRST STAGE REGULATOR

A	JULY '88	CONFIGURATION 4
REV.	DATE	

SCUBAPRO®

CAT. NO. 10-043-000